

mix it / spray it / finish it

MULTI RM40

PRODUCT DESCRIPTION

DMC MULTI RM40 is a pre-mixed multi purpose mortar mix specially formulated for Middle East conditions. All DMC products need only to be mixed with water.

MANUFACTURER

Dry Mortar Company T +966 1 499 2374
 PO Box 355 798 F +966 1 499 2367
 Riyadh E info@dmc-mix.com
 Saudi Arabia W www.dmc-mix.com

USE

DMC MULTI RM40 for all block laying, rendering and repair jobs.

Suitable for Exterior and Interior.

ADVANTAGES

DMC MULTI RM40 is part of an integrated wall system starting with block laying mortars to renders and mineral paints for a complete solution.

DMC combines materials and application technology for optimum quality, productivity and efficiency.

MULTI RM40 offers excellent adhesion, workability, durability and resistance to cracking. It is salt free, weather resistant and non-combustible.

It combines convenience and economy for all building purpose on projects of any size.

ENVIRONMENT

DMC values the environment. All DMC products use the the benefits of natural materials to reduce harmful substances, VOC and CO₂ emissions, wastage and enhance the living environment.

AVAILABLE SIZES

BAGS


20 kg bags

JUMBO BAGS

1200 kg bags

SILOS

ask for availability in your area



TECHNICAL DATA

COLOUR	Grey
APPEARANCE	Grey powder
BINDER	Cement
ADDITIVES	Contains additives to improve consistency & workability
MIXING RATIO	Add 20 kg to 6 lit of water
RECOMMENDED MINIMUM THICKNESS	10 mm
COVERAGE	(kg/m ² /mm) 0.5
STORAGE LIFE	12 months from manufacture under dry and sheltered conditions

APPLICATION

This product has been pre-mixed and needs only the addition of water. It contains special additives to improve workability and consistency.

MIXING can be done by hand, drill, batch mixer or by DMC mixing/spray machines. Always add the material to the water.

PREPARATION is done in the usual manner by lightly dampening the surface (must be free from dust, dirt and all manner of contamination). For low absorption, old or difficult surfaces apply one coat of **DMC BRIDGE SA90** by either spraying or using notch-trowel.

APPLICATION is by hand or DMC mixing/spray machines.

Special additives enhance working time and reduce moisture loss to brick/block work and surrounding environment. DMC recommends to apply the material in the shade. Ideal working temperatures are 5° to 35° C .

FINISHING can be done in a variety of textures and styles from smooth to highly textured. **DMC MULTI RM40** does not require a sealer either prior or after application.

SYSTEM

DMC MULTI RM40 is part of a complete rendering system.

PAINTING is recommended to be done with BAUWERK Mineral Paints, visit www.dmc-mix.com for more information.

DISCLAIMER

All information given on this technical data sheet is for general guidance only. DMC reserves the right to change specifications without prior notice; always refer to latest version at www.dmc-mix.com