

mix it / spray it / finish it

RENDER MM20

PRODUCT DESCRIPTION

DMC RENDER MM20 is a pre-mixed mineral base and finishing render specially formulated for Middle East conditions.

All DMC products need only to be mixed with water.

MANUFACTURER

Dry Mortar Company T +966 1 499 2374
 PO Box 355 798 F +966 1 499 2367
 Riyadh E info@dmc-mix.com
 Saudi Arabia W www.dmc-mix.com

USE

DMC RENDER MM20 for all rendering applications for a variety of finishes from smooth to textured without the need for sealers.

Suitable for Exterior and Interior.

ADVANTAGES

DMC RENDER MM20 is part of an integrated wall system starting with block laying mortars to renders and mineral paints for a complete solution.

DMC combines materials and application technology for optimum quality, productivity and efficiency.

RENDER MM20 offers excellent adhesion, workability, durability and resistance to cracking. It is salt free, weather resistant and non combustible.

As a permeable material it has heat and humidity regulating properties and reduces thermal stress.

ENVIRONMENT

DMC values the environment. All DMC products use the the benefits of natural materials to reduce harmful substances, VOC and CO₂ emissions, wastage and enhance the living environment.

AVAILABLE SIZES

BAGS

20 kg bags

JUMBO BAGS

1200 kg bags

SILOS

ask for availability in your area



TECHNICAL DATA

COLOUR	White
APPEARANCE	White powder
BINDER	White cement
ADDITIVES	Contains additives to improve consistency & workability
MIXING RATIO	Add 20 kg to 5 lit of water
RECOMMENDED MINIMUM THICKNESS	10 mm
COVERAGE	(kg/m ² /mm) 0.5
STORAGE LIFE	12 months from manufacture under dry and sheltered conditions

APPLICATION

This product has been pre-mixed and needs only the addition of water. It contains special additives to improve workability and consistency.

MIXING can be done by hand, drill, batch mixer or by DMC mixing/spray machines. Always add the material to the water.

PREPARATION is done in the usual manner by lightly dampening the surface (must be free from dust, dirt and all manner of contamination). For low absorption, old or difficult surfaces apply one coat of **DMC BRIDGE SA90** by either spraying or using notch-trowel.

APPLICATION is by hand or DMC mixing/spray machines.

Special additives enhance working time and reduce moisture loss to brick/block work and surrounding environment. DMC recommends to apply the material in the shade. Ideal working temperatures are 5° to 35° C .

FINISHING can be done in a variety of textures and styles from smooth to highly textured. **DMC RENDER MM20** does not require a sealer either prior or after application.

SYSTEM

DMC RENDER MM20 is part of a complete rendering system.

Painting is recommended to be done with BAUWERK Mineral Paints, visit www.dmc-mix.com for more information.

DISCLAIMER

All information given on this technical data sheet is for general guidance only. DMC reserves the right to change specifications without prior notice; always refer to latest version at www.dmc-mix.com