

mix it / spray it / finish it

TEXTURE TT20

PRODUCT DESCRIPTION

TEXTURE TT20 is a pre-mixed mineral texture finish for most types of wall surfaces, specially formulated for Middle East conditions.

All DMC products need only to be mixed with water.

MANUFACTURER

Dry Mortar Company T +966 1 499 2374
 PO Box 355 798 F +966 1 499 2367
 Riyadh E info@dmc-mix.com
 Saudi Arabia W www.dmc-mix.com

USE

TEXTURE TT20 for most wall surfaces where a sprayed-on texture is desired. The material allows for a variety of finishes depending on spray technique. Well suited for repaired surfaces to create a uniform finish.

Suitable for Exterior and Interior.

ADVANTAGES

TEXTURE TT20 is part of an integrated wall system starting with block laying mortars to renders and mineral paints for a complete solution.

DMC combines materials and application technology for optimum quality, productivity and efficiency.

TEXTURE TT20 offers excellent adhesion, workability, durability and resistance to cracking. It is salt free, weather resistant and non-combustible.

ENVIRONMENT

DMC values the environment. All DMC products use the the benefits of natural materials to reduce harmful substances, VOC and CO₂ emissions, wastage and enhance the living environment.

AVAILABLE SIZES

BAGS

20 kg bags

JUMBO BAGS

1200 kg bags

SILOS

ask for availability in your area



TECHNICAL DATA

COLOUR	White
APPEARANCE	White powder
BINDER	White cement
ADDITIVES	Contains additives to improve consistency & workability
MIXING RATIO	Add 20 kg to 5 lit of water
RECOMMENDED MINIMUM THICKNESS	10 mm
COVERAGE	up to 50 m ² / 20 kg
STORAGE LIFE	12 months from manufacture under dry and sheltered conditions

APPLICATION

This product has been pre-mixed and needs only the addition of water. It contains special additives to improve workability and consistency.

MIXING can be done by hand, drill or by DMC mixing/spray machines. Always add the material to the water.

PREPARATION is done in the usual manner by lightly dampening the surface (must be free from dust, dirt and all manner of contamination).

APPLICATION is by hand or DMC mixing/spray machines.

Special additives enhance working time and reduce moisture loss to brick/block work and surrounding environment. DMC recommends to apply the material in the shade. Ideal working temperatures are 5° to 35° C .

FINISHING can be done in a variety of textures and styles from lightly to highly textured.

TEXTURE TT20 does not require a sealer either prior or after application.

SYSTEM

TEXTURE TT20 is part of a complete rendering system.

PAINTING is recommended to be done with BAUWERK Mineral Paints, visit www.dmc-mix.com for more information.

DISCLAIMER

All information given on this technical data sheet is for general guidance only. DMC reserves the right to change specifications without prior notice; always refer to latest version at www.dmc-mix.com