

# Technical Data

## BENGALAC VARNISH



### Product description

Based on specially formulated alkyd modified urethane binder. It has excellent application properties which gives a good film build, dries to a tough film with outstanding durability.

---

### Recommended use

For use on wooden surfaces for interior and exterior

---

### Film thickness and spreading rate

	Minimum	Maximum	Typical
Film thickness, dry ( $\mu\text{m}$ )	25	30	30
Film thickness, wet ( $\mu\text{m}$ )	65	75	75
Theoretical spreading rate ( $\text{m}^2/\text{l}$ )	16.4	13.6	13.6

---

### Physical properties

Colour	Transparent
Solids (vol %)*	41 $\pm$ 2
Specific Gravity	0.88 – 0.92
Flash Point	40°C

---

### Surface preparation

The wooden surface must be clean, dry and properly sanded before application.

---

### Condition during application

The temperature of the substrate should be min. 3°C above the dew point of the air, temperature and relative humidity measured in the vicinity of the substrate.

---

### Application methods

Spray	Airless or conventional spray.
Brush	Recommended.
Roller	NA.

---

### Application data

Mixing ratio (volume)	Single pack.
Thinner/Cleaner	Jotun Thinner No. 2



---

## Packing size

1 US G.

Packing may vary from country to country according to local requirements.

---

## Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

---

## DISCLAIMER

*The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.*

Jeddah - Head Office	Riyadh (Branch)	Dammam (Branch)	Yanbu - Factory
Jotun Saudia Co. LTD	Jotun Saudia Co. LTD	Jotun Saudia Co. LTD	Jotun Saudia Co. LTD
P.O. Box 34698	P.O.Box 91586	P.O Box 4906	P. O. Box 30154
Jeddah - 21478	Riyadh 11643	Dammam 31412	Yanbu Al Sinaiya
Saudi Arabia	Saudi Arabia	Saudi Arabia	Saudi Arabia
Phone +966 02 6350535	Phone +966 01 2430503	Phone +966 03 8473090	Phone +966 04 3962911
Fax +966 02 6362483	Fax +966 01 2709689	Fax +966 03 8474097	Fax +966 04 3968483

Jotun is a World Wide company with factories, sales offices and stocks in more than 50 countries. For your nearest local Jotun address please contact the nearest regional office or visit our website at [www.jotun.com](http://www.jotun.com)

ISSUED MARCH 2005 BY JOTUN SAUDIA CO. LTD.  
THIS DATA SHEET SUPERSEDES THOSE PREVIOUSLY ISSUED