

# Technical Data

## JOTAGLUE



### Product description

Jotaglu for Jotafibre is based on a special homopolymer emulsion with excellent binding properties.

---

### Recommended use

It is used to fix Jotafibre range of wall coverings on the surface.

---

### Physical properties

Colour	White - Clear when dry.
Solids (vol %)*	26 ± 2
Specific Gravity	1.0-1.1
Typical Application	½ Ltr of glue per sq. mt of wall covering

---

### Surface preparation

A very porous surface may require a primer to avoid the glue being absorbed.

#### Other surfaces

The coating may be used on other substrates. Please contact your local Jotun office for more information.

---

### Condition during application

The temperature of the substrate should be min. 10°C and min. 3°C above the dew point of the air, temperature and relative humidity measured in the vicinity of the substrate.

---

### Application methods

Brush	Recommended.
Roller	Recommended.

---

### Application data

#### Note

Brush or roller. The glue should be applied on the wall over the full length and width of one section of Jotafibre. The Jotafibre should then be placed on the wall aligned with the vertical line or the last section of Jotafibre. Entrapped air should be squeezed out. Start from the center; push towards the edges by a wide trowel. The glue has a long "open time" giving a certain time for adjustment of the Jotafibre when hanging it on the wall.

---

## Drying time

Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly. The figures given in the table are typical with:

- \* Good ventilation (Outdoor exposure or free circulation of air)
- \* Typical film thickness
- \* One coat on top of inert substrate
- \* Relative humidity 70%

Substrate temperature	23°C	35°C	45°C
Surface dry	3 hrs	2 hrs	1 hr
Through dry	5 hrs	4 hrs	3 hrs
Dry to recoat, minimum	3 hrs	2 hrs	1 hr

The given data must be considered as guidelines only. The actual drying time/times before recoating may be shorter or longer, depending on film thickness, ventilation, humidity, underlying paint system, requirement for early handling and mechanical strength etc. A complete system can be described on a system sheet, where all parameters and special conditions could be included.

---

## Typical paint system

Fenomastic primer	1 coat
Stucco (If required.)	1 coat
JotaGlue	1 coat
Jotafibre (As per selected design or pattern)	
Fenomastic Gold, Silk or Matt	2 coats

Can also be used as glue for any fiberglass wall covering

---

## Storage

The product must be stored in accordance with national regulations. The product must be kept in a cool and well-ventilated place, protected from heat and direct sunlight. Containers must be kept tightly closed.

---

## Handling

Handle with care. Stir well before use.

---

## Packing size

18 Ltr

Packing may vary from country to country according to local requirements.

---

## Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

---

## DISCLAIMER

*The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.*

### **Jeddah – Head Office**

Jotun Saudia CO. LTD  
P. O. Box 34698  
Jeddah 21478  
Saudi Arabia  
Phone +966 02 6350535  
Fax +966 02 6362483

### **Riyadh – Branch**

Jotun Saudia CO. LTD  
P. O. Box 91586  
Riyadh 11643  
Saudi Arabia  
Phone +966 01 2430505  
Fax +966 01 2709689

### **Dammam – Branch**

Jotun Saudia CO. LTD  
P. O. Box 4906  
Dammam 31412  
Saudi Arabia  
Phone +966 03 8473090  
Fax +966 03 8474097

### **Yanbu – Factory**

Jotun Saudia CO. LTD  
P. O. Box 30154  
Yanbu Al Sinaiyah  
Saudi Arabia  
Phone +966 04 3962911  
Fax +966 04 3968483

Jotun is a World Wide company with factories, sales offices and stocks in more than 50 countries. For your nearest local Jotun address please contact the nearest regional office or visit our website at [www.jotun.com](http://www.jotun.com)

ISSUED MARCH 2005 BY JOTUN SAUDIA CO. LTD.  
THIS DATA SHEET SUPERSEDES THOSE PREVIOUSLY ISSUED