

Technical Data

JOTAFLOOR NON SLIP AGGREGATE TYPE - FINE / MEDIUM / COARSE



Product description

Jotafloor Non Slip Aggregate is pre-bagged graded, hard wearing aggregate designed to be applied in combination with Jotafloor products to give a non slip floor finish. Aggregate is cast on to wet material and the excess swept off when dry. Coverage depends on quantity initially used and desired profile.

Recommended use

Used where non slip areas are required in locations such as:

- ÿ Ramps
 - ÿ Warehouse aisles
 - ÿ Food Production Plants
 - ÿ Dairies
 - ÿ Production wet areas
 - ÿ Industrial slippery areas
 - ÿ Car parks
 - ÿ Traffic Deck Systems
-

Comments

Grades: Fine, Medium or Coarse (depending on texture required)

Coverage: 2 – 6 kg/m² gross - 1.5 – 4 kg/m² nett

Physical properties

Flash point Non-flammable

*Measured according to ISO 3233:1998 (E)

Condition during application

According to specifications for the chosen topcoat.

Application methods

Other If required Jotafloor Non Slip Aggregate can be used with Jotafloor Topcoat, Jotafloor Coating and Jotafloor SL Universal if required. (Advice should be sought from your local Jotun office regarding application techniques as these vary slightly from product to product).

Jotafloor Non Slip Aggregate is cast on to the wet first coat of the Jotafloor material until the whole surface is covered. Aggregate should not be thrown onto the wet coating as this may damage the first coat. Distribute the aggregate from a container eg. distribution sieve, that will allow the aggregate to fall directly onto the wet coating.

Once the first coat has dried, remove the excess aggregate from the surface by vacuum or sweeping brush for reuse if clean.

Apply the final coat of Jotafloor material to the desired thickness.

Storage

The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.

Handling

Handle with care. Stir well before use.

Packing size

Jotafloor Non Slip Aggregate Fine, Medium and Coarse supplied in 25 kg bags. Packing may vary from country to country according to local requirements.

Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.

Head Office & Nordic	Europe	Middle East	South East Asia
Jotun A/S	Jotun Paints (Europe) Ltd.	Jotun U.A.E Ltd. LLC.	Jotun (Singapore) Pte. Ltd.
P.O. Box 2021	Stather Road, Flixborough		No 11-15, Sixth Lok Yang
N-3248 Sandefjord	North Lincolnshire DN15	Al Quoz Industrial Area	Road
Norway	8RR	P.O Box 3671	Jurong
Phone +47 33 45 70 00	United Kingdom	Dubai U.A.E	Singapore 628 111
Fax +47 33 46 46 13	Phone +44 172 44 00 000	Phone +971 4 3 39 50 00	Phone +65 6265 4711
	Fax +44 172 44 00 100	Fax +971 4 3 38 06 66	Fax +65 6265 7484

Jotun is a World Wide company with factories, sales offices and stocks in more than 50 countries. For your nearest local Jotun address please contact the nearest regional office or visit our website at www.jotun.com

ISSUED 1 APRIL 2003 BY JOTUN
THIS DATA SHEET SUPERSEDES THOSE PREVIOUSLY ISSUED